



Indosati company in the field of providing to our valuable clients Ampoule Filing Machine. Developed and designed by the leading industry experts, these fillings are an important pharmacy instrument. The pistons are used to operate these ampoule fillings with the help of the electricity. These pistons have the property of the adjustment for the quantity of liquid tube filled. Burners are used for the sealing purposes. Moreover, these have smooth surfaces and are resistant to toxins.

Features:

Best quality
Strong and durable surface
Finds extensive utility in the industries

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568


Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eg to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



ANTIBIOTIC ZONE READER DIGITAL



We are a leading manufacturer of Antibiotic Zone Reader which is an ideal device for determination the strength of antibiotic activity, by measuring the diameter of inhibition zone in a Petri dish. Our Antibiotic Zone Reader measures the diameter of inhibition zone to 0.1mm within the range of 0-35mm. The special constriction of our Antibiotic Zone Reader consists of apparatus that gives light from source in the base and passes it through the transparent and semi transparent of agar, then to refluxed mirror supported by arm above the unit. The mirror reflects the light to the glass prism mounted at the front of unit and magnified image of the zone clearly visible on the prism. This amazing product has places us among the luminary Antibiotic Zone Reader manufacturers and suppliers based in Ambala Cantt.

Features :-

Diameter of inhibition zone in a Petri dish Diameter of inhibition zone to 0.1mm within the range of 0-35mm Special constriction

Widely Used In :Institutes
Medical Colleges
Industries
Pharmacy colleges and Industry
Laboratories
Hospitals
Pharmaceutical Industry

Manufacturers & Exporters

THE INDO SATI INSTRUMENTS & CHEMICALS

MEDICAL LAB D,B&M PHARMACY COLLEGES/INSTITUTIONS D & B D-U-N-S NUMBER -91-652-0568
Govt Reg. No.-NSIC/GP/NTP/2022/98624

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



ASEPTIC CABINET



Acrylic sheet front and side door, fully visible transparent, 3' germicidial ultraviolet tube and 2' flourescent tube for white light with necessary cock blast, starter and switches fitted. With mains lead and plug. Provided with two holes with rings and sieves for insertion of arms

Dimensions 95 x 50 x 50 cm with sloping front...

Same as above but fitted with small tube.

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131

INDOSATI

SCIENTIFIC LAB EQUIPMENT



PORTABLE AUTOCLAVE S.S. SEAMLESS/ALUMINIUM MODEL NO. - AB-06

- The sterilizer is made of S.S.Sheet deep drawn to cylindrical shape. The seamless construction allow no bacterial residue & free from dirt accumulation. It is equipped with dial pressure gauge 0-60 PSI, spring loaded safety valve, dead weight type safety valve and stream release valve.
- The load is held in dressing drums (optional), which is supported on a stand (tripod) the autoclave is hydraulically tested at twice the working pressure as per ISI requirement. It is fitted with ISI marked heater.
- Suitable to work on 220/230 volt. Single phase,50 hz,AC supply.

Available in following sizes:

Size 300 X 300 - 300 mm



INDOSATI



THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



BALL MILL



Product Details:

Electrically operated, motor driven made of stainless steel. Speed control.

Capacity:

- 1 litre mill made of stainless steel
- 2 litre mill made of stainless steel

acturers


THE INDO SATI INSTRUMENTS & CHEMICALS

MEDICAL LAB D,B&M PHARMACY COLLEGES/INSTITUTIONS D & B D-U-N-S NUMBER -91-652-0568

Govt Reg. No.-NSIC/GP/NTP/2022/98624

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131





B.O.D. INCUBATOR (LOW TEMPERATURE)

This the most versatile low temperature indicator for biochemical oxygen demand determination. Caster wheel mounted cabinet is double walled with inner chamber Of anodized aluminum of stainless steel and outer casing of M.S. sheet duly painted. The gap of 75 m.m. between the outer and the inner wall is filled with special grade glass wool to prevent thermal losses. Triple walled back of the unit is fitted with two air circulation fans for maintaining temperature uniform ally through the chamber. Heating elements of nicrome wire are placed in the air path and are duly insulated from the body. The inner chamber is ribbed for placement of shelves at desired height. Full view inner glass door permits inspection of specimens, without disturbing the same, lock and key arrangement Is provided in the double walled outer door. Unit is fitted with door operated illumination lamp inside the chamber.

The temperature range from 5 degree c to 50 degree c is controlled by digital controller. Refrigeration unit is formed by Hermetically sealed isi marked compressor and the cooling coils are distributed all round the chamber and lie in the air circulation path. An I-shaped prismatic Thermometer is provided at the top on the front panel along with separate indicator lamps for mains, heating and incoming voltage. Supplied complete with 3 shelves, cord and plug to work on 220/230vA.C. Supply.

OPTIONAL ACCESSORIES

- B.O.D. Incubator with vertically illumination with 3 numbers of fluoroscent tubes of 60 cm. length placed vertically along the back wall, separate on/off switch for tubes.
- B.O.D. Incubator incorporated with tiumer 0-24 hour for regulation cyclic at an extra cost.
- Digital temperature indicator cum controller with PT-100 sensor at an extra cost instead of mercury thermometer.

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eg to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



BOTTLE WASHING MACHINE





Description-

Introduction – you can easily know about the parts of machine to see the above picture.

How to use -

- 1. Unpack the machine and sit it on a leveled floor.
- 2. Joint the water inlet connection with water line and set the drain water line as your convenience.
- 3. Plug in the machine and switch ON.
- 4. Open the tap and wash the bottle from outside as well as inside by the help of bottle inlet jets.
- 5. Scrub the bottle with brushes and wash it with water as your convenience.

Precautions -

- 1. Take care about your body parts when machine rotates.
- 2. Clean the machine after use.
- 3. Always wear gloves.

Manufacturers & Exporters

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



BULK DENSITY TEST APPARATUS





Owing to the consistent efforts of our dedicated team of professionals, we have been constantly engaged in offering the best quality array of Bulk Density Apparatus.

Features:

Less maintenance Sturdy design Rust proof body Thermostatic Timer Seed Knob

THE INDO SATI INSTRUMENTS & CHEMICALS

MEDICAL LAB D,B&M PHARMACY COLLEGES/INSTITUTIONS

D & B D-U-N-S NUMBER -91-652-0568 Govt Reg. No.-NSIC/GP/NTP/2022/98624

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131

INDOSATI

SCIENTIFIC LAB FOUIPMENT



CAPSULE FILLING MACHINE

CONSISTING OF:

- Versatile level operated consisting one plate for putting of capsule by hand.
- Removal of capsule.
- Filling of powder by dispensing of brush pressing.
- Fixing of capsule and sealing.
- Injection of capsules.



Model No. AB-383

All contact parts are made of Stainless Steel / Brass.

Available capacity 100 capsule.

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131





Revolutionary General Purpose Lab. Centrifuge Digital, Maximum speed 5200 Capacity-4x50ml

Model :AB-186

Microprocessor base Square M S body duly powder coated. Double walled light weight ABS lid. Fitted with microprocessor based 2 lines 16 characters LCD pannel for 0-59 minutes countdown timer, digital rpm meter and programmable speed. controller.

Manufacturers & Exporters

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



Owing to the expertise of our professionals, we have been manufacturing and supplying a range of premium grade Centrifuge Machine This centrifuge machine is fixed with a base and a rotating element where the mixture is revolved at a high speed. One of the important features of our Laboratory Centrifuge Machine is that it has high tensile strength, which helps it in revolving at a strong force. Using centrifugal force, the machine is capable of rotating the material of different densities easily. It is capable of separating solid and liquid parts of the and helps in purifying the vaccines.

Technical specification:

This centrifuge having better speeds and capacities fitted with resiliently mounted motor for vibration free performance and 5 step regulator

Body made of steel duly powder coated paint finish.

Round lid with handle available in 8 tubes

Suitable for 8 test

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131





CHEMICAL BALANCE



We are manufacturing a wide array of Chemical Balance for our customers.

Technical Specifications:

Beam:

Short beam of hard brass

Upper edge divided into 50 scales divisions to each side

Each scale division representing 1/5 mg

Rider on the scale

Stand: all parts of brass

Arrester: vertical raising type

Pans: chromium plated, slightly concave inwards

Case: wooden polished case, with front slider and two side doors.

Base: sun mica black board

Capacity: 200gms Sensitivity: 1/5 mg

Features:

Precise measurement

Durable

High accuracy

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131





COLONY COUNTER MODEL NO. - AB-152



An ideal instrument for counting bacterial mould colonies in culture work. It provides uniform glare free illumination to minimize strain on eyes and clearly define even small colonies. A 100 mm dia lens covers the entire illumination field and its magnification assures highly accurate results. Counting plate with standard Wolfhugel ruling ensures clearly differentiated and sharply defined colonies. Supplied complete with counting plate, lens, cord and plug. To work on 220VAC supply.

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131





COOKS POLE CLIMBING



Voltage : 200 V AC 50 Hz Phase : Single Phase

Outer chamber made of thick plywood sheet with an observation window and inner animal chamber is made of clear acrylic sheet bottom of which is provided with chrome plated brass bars.

A shock for controlled duration of 200V AC 50Hz single phase - 0.2ma is builtin and is controlled by builtin 11 position solid state timer upto 30 seconds. Output for connection to kymograph or recorder has been brought out as terminal. An animal dropping removal tray has been provided for keeping the equipment clean.

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



DIGITAL ACTOPHOTOMETER





The Digital Actophotometer provided by us consist of six built in photo sensor and four digital counters to indicate the loco meter activity. Our Digital Actophotometer measures the spontaneous and indicated activity with digital totalizes. It also incorporates electric shock of upto 100volts for activating rats. Our Digital Actophotometer can measure stimulus of is variable from 0-100volt and indicating on meter.

Features :-Six built in photo sensor Four digital counters Measures the spontaneous and indicated activity Incorporates electric shock of upto 100volts

Manufacturers & Exporters

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131





DIGITAL HOT AIR OVEN

Product Details:

Material : Mild Steel

Temperature : 5 degree Ambient to 250°C

with accuracy +/-3°C

Voltage : 220 VAC

Indosati has achieved milestone in offering Hot Air Oven Universal Digital to the clients. Hot Air Oven Universal Digital is manufactured at multifaceted infrastructure facility using high quality spare parts and components. Offered range is widely demanded by chemical, petrochemical, food and beverage and many industries. This product has great technical air blower and have gives consistence performance. Offered range provides vacuum drying for non-flammable and flammable solvents and ensures safe drying without residues or oxidation.

Features:

Long service life
Easy to handle
Low maintenance

Specifications:

Standard double wall construction. Outer made of mild steel duly enamel painted or powder coated paint, inner made out of stainless steel sheet. Heating elements provided at bottom & two sides Temperature controlled by hydraulic type of thermostat or Digital temperature controller. It is provided with (HxWxD) (With two SS shelves.

With two SS shelves.	ir
Optional Accessories:	30
Air Circulation Fan	35
Timer 0 – 24 Hours	40
Digital Timer	45
Digital Temperature Indicator	60
Digital Temperature controller –cum- Indicator	60
	90
LED	90
- The state of the	90

	Etherm M-778	HOT AIR (OVEN	OFF HEATH	
A. C. C.					
				v	

rechnical Details:						
	Chamber size	Chamber size	No.	Capacity		
th	(HxWxD) in mm	(HxWxD) in Inches	of shelves	in Litres		
	300 x 300 x 300	012 x 12 x 12"	2	28		
	350 x 350 x 350)14 x 14 x 14"	2	45		
	400 x 400 x 400	016 x 16 x 16"	2	65		
	450 x 450 x 450	018 x 18 x 18"	2	95		
	600 x 450 x 450)24 x 18 x 18"	2	125		
	600 x 600 x 600)24 x 24 x 24"	2	224		
in	900 x 600 x 450	036 x 24 x 18"	2	252		
	900 x 600 x 600	036 x 24 x 24"	2	336		
	900 x 900 x 900)36 x 36 x 36"	2	720		

THE INDO SATI INSTRUMENTS & CHEMICALS

MEDICAL LAB D,B&M PHARMACY COLLEGES/INSTITUTIONS

D & B D-U-N-S NUMBER -91-652-0568 Govt Reg. No.-NSIC/GP/NTP/2022/98624

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131







MODEL NO. - AB-20

DIGITAL INCUBATOR MODEL NO.-AB-20

- These are sturdy double walled units with outer chamber made of MS sheet duly enamel painted with inner made up of anodized aluminum or high SS sheet. The gap between inner and outer chamber is filled with high grade glass wool to avoid thermal looses. heating elements are placed in ribs ,at bottom and sides .Inner chamber is provided with ribs for adjusting perforated shelves to convenient height. The door is fitted with glass viewing window to facilitate inspection of samples without disturbing the test temperature.
- ☐ Temperature is controlled by digital controller from ambient to 70 degrees Celsius +-5 degree

Air ventilators are provided on the sides of the unit.

The unit works on 220/230VAC supply.

- □300x300x300 (12"x12"x12")
- □350x350x350 (14"x14"x14")
- □400x400x400 (16"x16"x16")
- __450x450x450 (18"x18"x18")
- □600x450x450 (24"x18"x18")
- □600x600x600 (24"x24"x24") □900x600x450 (36"x24"x18")
- □900x600x450 (36 x24 x 16)
 □900x600x600 (36"x24"x24")
- □900x900x900 (36"x36"x36")
- ☐ Air circulating fan to cost extra.
- □Digital temperature indicator cum controller (while ordering for an incubator with an digital controller, air circulating fan is considered compulsory and should be ordered along with it)
- Timer (0-24 hours) to cost extra.

Capacity-100 litre, Inner Chamber made up of Stainless steel With Fan

THE INDO SATI INSTRUMENTS & CHEMICALS

MEDICAL LAB D, B&M PHARMACY COLLEGES/INSTITUTIONS

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg. No.-NSIC/GP/NTP/2022/98624

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



MED. PHARMACY LAB INSTRUMENTS TRADE MARK NO.-4463564



DIGITAL PH METER (PID) 3 POINT CALIBRATION



DESCRIPTION:-

pH Meter is an instrument that measures the hydrogen-ion activity in water based solutions indicating its acidity or alkalinity expressed as pH.

The device measures the difference in electric potential between a pH electrode and a reference electrode. This difference in potential relates to acidity or pH of the solution.

Product Code: INDO-AB-144

Technical Specifications

Type Micro controller Based
PH Range 0.00 ph to 14.00 p
Display 3-1/2 Digit LED Display

Range 0.00 ph to 14.00 ph , 0 to ± 1999.9mv

Temp -20.0 to 150° C

Resolution 0.01 pH , 0.1mv , 0.1° C

Accuracy ± 0.05%

Temperature Compensation Automatic

Auto Buffer Recognition 4.00, 7.00, 9.20

Calibration 3 point

Memory storage of 100 samples 275 x 187 x 94mm (approx)

Power 220V ± 10V AC

Accessories pH Electrode, pH Stand, temp. probe,

3 Buffers: 4.00, 7.00, 9.20, Operating manual

Manufacturers & Exporters

THE INDO SATI INSTRUMENTS & CHEMICALS


AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



DIGITAL SIEVE SHAKER TABLE TOP MODEL



we are presenting for our clients a vast range of Sieve Shaker - Table Model. As per the specific clients' requirements, this shaker is available with FHP electric motor inside the body. Apart from this, adroit professionals use quality proven components and the latest technology in line with industry norms. Speed can be regulated in this shaker through an unceasingly variable speed regulator placed to the unit.

Features:

Safe usage Easy operation Less maintenance

General Description & Specification:

Digital Time switch 0-99 minutes for above Mechanical Time switch 0-60 minutes for above

Manufacturers & Exporters

THE INDO SATI INSTRUMENTS & CHEMICALS

MEDICAL LAB D,B&M PHARMACY COLLEGES/INSTITUTIONS

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg. No.-NSIC/GP/NTP/2022/98624

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131





DISINTEGRATION TESTING MACHINE



Our Disintegration Testing Machine is fitted with a motorized shaft moves in and up and down direction at a frequency of 30 cycles per minute. It can hold 6 glass tubes of standard size with stainless steel wire gauge bottom. Our Disintegration Testing Machine has a cylinder which can moves up & down with standard dish inside in a 1Ltr.Beaker filled with distilled water which is maintained at 30oc by thermostatically controlled hot plates(without beaker)

Features :-

Used for the determination of disintegration of time of tablets Fitted with a motorized shaft Rotation at frequency of 30 cycles per minute Can hold 6 glass tubes of standard size

Variants :-Single basket Double basket

Manufacturers & Exporters

THE INDO SATI INSTRUMENTS & CHEMICALS

MEDICAL LAB D.B&M PHARMACY COLLEGES/INSTITUTIONS

D & B D-U-N-S NUMBER -91-652-0568 Govt Reg. No.-NSIC/GP/NTP/2022/98624

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131





DISSOLUTION TEST APPARATUS



For (1) SINGLE TEST (2) THREE TEST (3) SIX TEST Used for tablet to dermine th durability at the time of production .. The apparatus consists of the following:

Transparent plastic perpex Bath with cover. 1000 cc vessel made from Corning Glass. Bath is fitted with 500 Watts heater. A F.H.P. ELECTRIC MOTOR provided with electronic speed regulator which varied from 25 R.P.M TO 250 R.P.M approx. A stainless Steel stirring Rod fitted with Electic Motor to rotate smooth and without any perceptible wobble in the vessel. A thermostat is provided to maintain water temperature at 37C only distilled water should be filled in Bath before operation. Complete unit supplied with 3 core and plug to work on 220 Volt A.C.

Manufacturers & Exporters

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131





DOUBLE CONE BLENDER



Introduction – you can easily kn<mark>ow</mark> about parts of the machine to see the above picture. Capacity 5k.g

Uses of double cone blender -

The double cone Blender is a tumble blender intended for laboratory applications. Consist of two S.S cone welded with the cylindrical shell and having charging and discharging at opposite ends. As the cone shaped blender shell rotates, the tumbling action splits the powder or liquid bed and then combines it, bringing about the mixing of the ingredients. The result is a consistent, uniform, predictable blend.

How to use -

- 1. Loose the cover of shell.
- 2. Fill the equal or as you desire to mix the material in cone shell.
- 3. Tight the covers properly and switch ON the machine. The blender starts tumbling the material and consist it. Mix the material as per your requirement.
- 4. Switch OFF the machine. Open the cover of out put neck and collect the consisted material.

Manufacturers & Exporters

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131





ANALGESIOMETER EDDY HOT PLATE





We have marked a dynamic position in the market by providing the finest quality range of Analgesiometer Eddy Hot Plate.

Features:

Easy functionality Rugged design Easy to use

Description:

Offering Analgesiometer Eddy's Hot Plate With square box consisting of 30x30cms, heating surface with Perspex enclosure and solid state digital temperature controller with indicating galvanometer to set surface temp. Between 30°to 80°C.

Manufacturers

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



ELECTRO-CONVULSIOMETER DIGITAL





The Electro- Convulsiometer is the instrument used for applying maximal Electro shock through the corneal electrodes provided with the instrument. It is used to study the anti-convulsant activity of phonation against maximal electro shock induced convulsions in rats.

Product Specification

Display Type Digital +-2%

Timer 0.1sec. to 3 sec

Power Source Electric

Weight (kg) 5Kg Approx.

Manufacturers & Exporters

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eg to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



FRIABILITY TEST APPARATUS



Used to determine the durability and abrasives of tablets a transparent Perspex (Made of imported Perspex sheet 6.4 mm thick) 300 mm dia x 35 mm deep and white cover disc and nut also a shaped radial fixed blade which carries the tablets along with it up to the central height and lets them off while the drum is rotating thus the tablets rub against each other without any hard impact the drum rotates at a fixed speed of 30 R.P.M by a geared motor and the rotations period is controlled by a timer (imported time switch duration 1 to 15 minutes) per determined end preset the motor unit is housed in a shaped steel cabinet with shaft extended on one side upon which the drum rotates switches with neon indicators and time switch are fitted on a panel and provided work on 220 volts 50 C/s A.C

THE INDO SATI INSTRUMENTS & CHEMICALS


AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



HAEMOCYTOMETER



Haemocytometers with red and white Pipettes

Neubar Counting Chamber -made of toughedned glass, size approx: 3 x1.2

With central ridge and two furrows of depth 0.1mm, 1/400mm2 should be supplied with RBC pipette and WBC pipette and cover slips.

THE INDO SATI INSTRUMENTS & CHEMICALS

ANISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



HEMOGLOBINOMETER (SAHIL'S)



Model: AB-168

Indosati offer the Haemoglobinometer square tube type
The kit consists of following standard setup:

Comparator Holder: 1 No.

It is black in colour. The back of the holder is fitted with milky colour screen made of acrylic. In front of the holder there are three windows. The two side windows are fitted with colour standard strips and middle window is meant for the square tube for colour comparison. The size of all the three windows are Height 3 cms. and Width 0.5 cms. (Minimum)

Square H.B. Tube: 2 Nos. (Square H.B. Tube is graduated on both the side for the measurement of haemoglobin in respect of percentage and gram .)

H.B. Pipette: 1 No. (20 microlitre H.B. Pipette with latex tube and mouth piece)

Amber coloured glass bottle -1 No.
Glass Stirrer -1 No.
Dropper with teat -1 No.
Cleaning Brush -1 No.
Spare latex tubing one meter -1 No.

Manufacturers & Exporters

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



HEATING MANTLE

(MADE OF GLASS YARN)

Suitable for laboratories, chemicals, pharmaceuticals, Dyes, Glass plants etc. Particularly useful for Heating inflammable liquids. Electric heating net is hand knitted from glass Yarn and there is no joint to maintain the strength of the yarn and stands high temperature up to 350 degree c. the body of the mantle is spun one piece from non-rusting Aluminum (up to 5.0 liters Capacity) duly stoving painted. All heating mantles are lagged with special grade mineral wool.



To work on 220/230 Volts AC.

Available in various capacities from 50ml to 200 liters.

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



HOT PLATE ROUND



Mounted on a thick M.S. sheet body, a smooth surface cast iron plate fitted with an electrically operated element laid under the plate. A three step rotary switch works on 220/230 volts A.C. controls heating. The plate is finished in heat resistant black and the body in stoved blue white.

Double Round 20 cm (8") dia, electrically operated, 3 Heat Switch with cord and plug.

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



INFRARED MOISTURE BALANCE



Product Specification

Measuring Range :0-100% :0.2% Readability : +2% Accuracy

Mains : 230 Volts, 50 Hz

:5 or 10 or 20 or 25 gms. Capacity

Disposable Pans Pains Forceps

Thermometer :1

Product Description

High Performance compact dependable measurement of moisture content of materials not effected by radiation why loosing water under moisture exposure.

Infra Red Moisture Balance

A high performance compact, dependable infra-red Moisture Balance for measurement of moisture content of materials not affected by radiation while loosing water under of moisture exposure to infra-red radiation.

The 250W infrared lamp gives great generation of heat which is controlled by auto transformer. The balance is calibrated in terms of moisture percentage 0-100% and is read directly on the instrument.

Widely used for

Testing soils n Agriculture soils Chemicals

Raw materials n Food Pharmaceuticals

Plastics and similar materials.

THE INDO SATI INSTRUMENTS & CHEMICALS AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



KYMOGRAPH



Application : Laboratory, Industrial

This is an electrically driven recording drum or kymograph suitable for use by students for lab. Experiments. These Kymographs are also used to measure atmospheric pressure, tuning fork vibrations and functioning of steam engines.

Its drive mechanism consists of constant speed heavy duty electric motor and an accurate gear box contained in the base together with robust plate clutch. Engagement of various gear ratios are affected by sliding the lever into the slot marked with surface speed or by a knob.

The recording drum or cylinder has a 6' dia and stainless steel spindle have been standardized to make the same universal and interchangeable. It has 8 variable speeds. The speed is measured in mm per second. Eight variable speeds are 0.12, 0.25, 1.25, 2.5, 12.5, 2.5, 3.20 and 6.40 mm per second. A hand gear is provided to change the speed of the kymograph.

Double electric contact arms are clamped on the main spindle and a stout double-contact block is fitted on top of the base. It runs on 220V, AC 50Hz.

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131





LABORATORY AGITATOR



Specifications:

Application: For Special All Type Of Solvents Used In Laboratories

Capacity: Up 50 Liters

Type Of Blades: Special As Per Requirement

Motor Hp- Upto 2.0 Hp

Extra Accessories: Rpm Controller.

Special Features: Heavy Platform, Up & Down Motion With Gear Box, Rpm

Controller.

Fitted with speed regulator, height and space adjustable. 1/20 H.P. AC/DC motor

Manufacturers & Exporters

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568


Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



LAMINAR AIR FLOW (HORIZONTAL) WOODEN



Pre-filter: 99.00% down to 5 micron.

HEPA Filter: ISO 14644 Class 5 (Class 100) 99.97%-99.99% down

to 0.3 micron. Mesh guard for protection of HEPA Filter.

Airflow: Frontward Horizontally.
Noise Level: 60 decibel ± 5%.
Velocity: 0.35-0.50m/sec.

Work Table: Made up of Stainless Steel 304gr. Cock for gas on work table.

Side Panels: 6mm ± .5mm thick acrylic sheet.

Front door: Made of acrylic.

UV Lamp: 15/30W, make Philips Holland

Illumination: 20/40W, Fluorescent tube with diffuser. Pressure: Inclined Manometer 0-50mm range. Power Supply: 230V ± 10V/50Hz single phase A.C.

Cabinet: 19mm thick Duraboard Covered with sunmica from outside and epoxy painted from inside. Heavy Duty Blower: Dynamically balanced with 0.25 HP Electric Motor Mounted on anti vibration

pad1440rpm motor.

Indosati Working area size 60x60x60 cm. Indosati Working area size 90x60x60 cm. Indosati Working area size 120x60x60 cm. Indosati Working area size 180x60x60 cm.

Manufacturers & Exporters

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eg to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)


Tel No.: 0091-171-4000131 / 4001131





LIQUID FILLING MACHINE





- 2. Capacity adjustment screw with level scale left hand side
- 3. Licqued feeling inlet vassal back side near operating handle
- 4. Bottle stand fount
- 5. Outlet tap fount

HOW TO OPERATE

- 1. Fix the machine on the floor
- 2. Fill the liquid in vassal cap. 5 liter
- 3. Adjust the capacity screw on the level scale
- 4. Put the bottle on the stand
- 5. Rotates the handle clockwise
- 6. Fill the bottle

PRECAUTIONS

- 1. Clean and cover the machine after use
- 2. Unfilled the machine if not in use
- 3. Take care about your hand while rotates the handle

Manufacturers & Exporters

THE INDO SATI INSTRUMENTS & CHEMICALS

MEDICAL LAB D.B&M PHARMACY COLLEGES/INSTITUTIONS

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg. No.-NSIC/GP/NTP/2022/98624

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131





MAGNETIC STIRRER DIGITAL MODEL NO-AB-64





It has a compact stirring device utilization a rotating magnetic field (created by a PERMANENT MAGNET) which induces variable speed stirring action. Stirring is accomplished by means of small TEFLON rotor, which when placed in the liquid to be stirred is capable of rotation by magnetic field applied from below the container. The unit is fitted with pilot lamp. To work on 220/230 volts A.C. available with or without hot plate (as required).

Available Capacities

1 Litre

2 Litres

5 Litres

10 Litres

THE INDO SATI INSTRUMENTS & CHEMICALS

MEDICAL LAB D,B&M PHARMACY COLLEGES/INSTITUTIONS D & B D-U-N-S NUMBER -91-652-0568

Govt Reg. No.-NSIC/GP/NTP/2022/98624

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131





MAGNETIC STIRRER



It has a compact stirring device utilization a rotating magnetic field (created by a PERMANENT MAGNET) which induces variable speed stirring action. Stirring is accomplished by means of small TEFLON rotor, which when placed in the liquid to be stirred is capable of rotation by magnetic field applied from below the container. The unit is fitted with pilot lamp. To work on 220/230 volts A.C. available with or without hot plate (as required).

Available Capacities

1 Litre

2 Litres

5 Litres

10 Litres

THE INDO SATI INSTRUMENTS & CHEMICALS

MEDICAL LAB D, B&M PHARMACY COLLEGES/INSTITUTIONS

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg. No.-NSIC/GP/NTP/2022/98624

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131





MECHANICAL STIRRER



Product Details:

DC Motor RPM : 100-4000 RPM Material : Stainless Steel

Shaft length : 250 mm Shaft dia : 6-8 mm Maximum Speed : 4000 RPM

Mechanical stirrer is an apparatus with noise less universe motor, maximum speed with electronic variable speed regulator between 200 to 4000rpm. The stirrer shaft is of stainless steel with 3 bladed propeller having 37mm.sweep, shaft and stirrer coupled by mean of simple bush coupling with grub screw.

Capacity

With 1/20 H.P. Motor With 1/20 H.P. Motor

With 1/8 H.P. Motor

With 1/8 H.P. Motor

With 1/4 H.P. Motor

With 1/2 H.P. Motor

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eg to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131





MONSANTO TYPE TABLET HARDNESS TESTER



A fairly handy instruments for taking quick readings for the hardness of tablets. It is made of brass turned parts, heavily chrome plated, the scale is 0 to 20 kg and the index mark and division is in 1 kg reading. Scale adjustable for zero setting as per size of the tablets.

Manufacturers & Exporters


AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



MUFFLE FURNACE WITH PYROMETER



- Light weight with ceramic fiber wool insulation (instead of brick insulation). The outer casing is made of double walled thick P.C.R.C. sheet, duly painted. Heating elements are made of KANTHAL "A-1" wire and backed by high temperature cerwool insulation, which avoids loss of energy. Temperature control unit consist of energy regulator, fitted in front of furnace with two pilot lamps. The apparatus is complete with one pyrometer, thermocouple, Silver thermal fuse main lead with power plug. (AB-56)
- To work on 220/230 volts or 400/440 volts A.C. maximum temp. is 1000 degree C and working temp. 900 degree C.
- □100 x 100 x 225 mm
- ☐ 125 x 125 x 250 mm
- □125 x 125 x 300 mm
- □150 x 150 x 300 mm
- □200 x 200 x 300 mm
- □175 x 175 x 475 mm
- □300 x 300 x 300 mm

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



OINTMENT FILLING MACHINE



Stroke type machine. With heavy stable base. Filling capacity adjustable from 5 gm. to 50 gm. Detachable nozzles provided for each capacity. Hooper and contact parts are of stainless steel.

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



STUDENT ORGAN BATH MODEL NO. - AB-352



Upright, organ tubes, frontal lever from capillary tubing ¾ it capacity. Thermostatically controlled. The illustrated has bath has been designed mainly for students experiments with smooth muscle etc. it is however quite suitable for general use. The water container of the bath consists of a bottomless screw cap jar of app. ¾ liters capacity fitted into a threaded metal stand in which is also located a wire wound heater to maintain the water temperature. A glass inner vessel passes through the stand and is insulated so that the fluid can be quickly run out. Depending in the vessel is a platinum-tipped oxygen tube which is firmly held by means of screw clamp fixed to one of the stand uprights. Overall height of bath 15 cm.

THE INDO SATI INSTRUMENTS & CHEMICALS

MEDICAL LAB D,B&M PHARMACY COLLEGES/INSTITUTIONS D & B D-U-N-S NUMBER -91-652-0568

Govt Reg. No.-NSIC/GP/NTP/2022/98624

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131





PHYSICAL BALANCE



We offer Physical Balance used for measuring the weights. Analytical balance made of aluminum alloy which is a highly sensitive balance having 200gm and having a capacity and sensitive to 0.1mg. The balance is staged on synthetic back board and box is made of wood which is well polished and the rider scale is fitted in front of the beam which contains 100 Notches with zero at the center, vertical rating type on knives and planes. These are available at affordable price in the market.

Manufacturers

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131





PROJECTION MICROSCOPE



Technical Specifications:

Microscope Body is heavy duty, inclined monocular type with sturdy base. Equipped with Coarse & Fine Focusing systems with Quadruple revolving Nose Piece. Plain stage (120x120mm) with graduated Mechanical Stage for X-Y movements of specimen slide.

Built in light by 6V-20W halogen lamp with continuously variable light intensity control. The whole system of condenser & light arrangement is moveable up & down by rack & pinion to get the optimum results.

Projection Doom of screen size 150 mm is rotatable through 360°.

Objectives: Achromatic 10x & 20x/40x (SL)

Projection Eye Piece: 10x (Huy)

Packed in a thick and attractive plywood box

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



ROTA ROD-II COMPARTMENTS





The Rotarod Apparatus provided by us come with latest with digital counter, for determining neuro-pixicity, muscle tone, balance and motor co-ordination in rats and mice. Our Rotarod Apparatus have two or three or four compartments of 75mm width each with a rotating rod of 25mm diameter having speeds of 5,10,15,20 and 25 r.p.m with time interval countries in each compartment.

Variants:-Two compartments Three compartment.

Manufacturers & Exporters

THE INDO SATI INSTRUMENTS & CHEMICALS

MEDICAL LAB D,B&M PHARMACY COLLEGES/INSTITUTIONS D & B D-U-N-S NUMBER -91-652-0568

Govt Reg. No.-NSIC/GP/NTP/2022/98624

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131





SOXHLET EXTRACTION UNIT



Bath type for 100 to 350 ml flasks with one energy regulator for controlling all baths individual ON/OFF switches without glass parts. Two adjustable rods with clamps.

- → Unit of 3 test with ON/OFF switches. (Hot Plate Type)
- → Unit of 3 test with ON/OFF switches. (Mantle Type)
- → Unit of 6 test with ON/OFF switches. (Hot Plate Type)
- → Unit of 3 test with ON/OFF switches. (Mantle Type)

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



SPHYGMOMANOMETER DIAL TYPE





Product Specification

Type

Power Source

Cuff Type

Weight

Measurement Range (Pressure)

Measurement

Cuff Size 1

Accuracy

Usage/Application

Color

Dial type

Manual

Yes

300 gm

0-300 mm Hg

Upper Arm

8-22 cm

0.01 (pressure)

Hospital, Medical Lab

Black, Green

Manufacturers & Exporters

THE INDO SATI INSTRUMENTS & CHEMICALS

MEDICAL LAB D,B&M PHARMACY COLLEGES/INSTITUTIONS D & B D-U-N-S NUMBER -91-652-0568

Govt Reg. No.-NSIC/GP/NTP/2022/98624

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



With our vast industrial experience, we are engaged in offering large array of Digital Sphygmomanometers. We offer products to our patrons as per their needs and technically advanced. Our Digital Sphygmomanometers are highly recommended amongst the clients for their long functional life. Moreover, our Digital Sphygmomanometers is reliable too.

Features:

BLOOD PRESSURE MONITOR-UPPER ARM

- 1. It is very simple to use due to its One-Touch operation
- 2. Irregular Heart Beat Detection
- 3. Body Movement Detection
- 4. Memory for last reading
- 5. Hypertension Indicator
- 6. It has a big display for easy reading

Easy to use Effective Affordable

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



SPIROMETER



Spirometer mainly used as Gasometers in the Research Labs, Medical institutions and many other Labs. These are featured with the 6 liter of vital capacity; with chain compensate counter balance to float through pulley, calibrator to denote volume, inlet, & outlet tubes, stainless steel chamber; complete with corrugated rubber tubes. For the manufacturing and supplying of these Spirometers, we have positioned an apex.

Acknowledged For :Use as a Gasometers
6 liter of vital capacity
Chain compensate counter balance to float through pulley
Calibrator to denote volume
Inlet, & outlet tubes
Stainless steel chamber
Corrugated rubber tubes

Manufacturers & Exporters

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



STERILITY TESTING SINGLE UNIT





Description-

It is as per our standard design it consists os stainless steel flask with stainless steel clamps and stainless steel support screen made out stainless steel 316 quality single station without stand.

Usage/Application Lab

Brand Indosati

Capacity 250 ml

Diameter 3-47 mm

Country of Origin Made in India

Frame Material Stainless Steel

Material Grade SS 304, SS 310

Automation Grade Manual

Manufacturers & Exporters

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



SCIENTIFIC LAB EQUIPMENT



STETHOSCOPE



Chest Piece Material : Stainless Steel

Condition : New

Features : Dual Head
Type by Practice : Physician
Types : Acoustic
Use : Medical

In order to fulfill various demands of our esteemed clients, we are engaged in providing an optimum quality array of Stethoscope.

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131







DESCRIPTION:-

Body:-Well designed heavy & sturdy die-casted monocular body inclinable to 90° suitable to meet the needs of college and school students.

Tbe with mechanical length 160mm.

Focusing by separate coarse fine focusing knobs with triple revolving nose piece, horse shoe base.

Square stage 120x120mm with clips for holding the slide.

Double lens bright field ABBE Condenser(N.A. 1.25) is fixed with the stage with iris diaphragm and swing out filter holder.

Illumination by plano concave mirror in fork mount.

Optical Combination:

Anti Fungal Objectives:4/5x, 10x, 45x(SL)

Eye Piece:10x, 15x(Huygenian)

Packing: In the rmocouple case with dust cover.

Manufacturers & Exporters

THE INDO SATI INSTRUMENTS & CHEMICALS

MEDICAL LAB D, B&M PHARMACY COLLEGES/INSTITUTIONS

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg. No.-NSIC/GP/NTP/2022/98624

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



TABLET COATING PAN:

Made of stainless steel dia 12". Machine fitted with oil-immersed gear box driven by a suitable motor. An independently working hot air blower has been provided. An energy regulator has been provided to control temperature from 5°C above ambient to 70°C. A separate switch for the blower has been provided. Complete with neon indicator. Machine to work on 220V AC 50 Hz single phase.

Via macturers

THE INDO SATI INSTRUMENTS & CHEMICALS


AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



TABLET PUNCHING MACHINE

INDOSATI



Tablet Making Machines are used for the making of tablets up to 1000mg. and as per size of die and punch 6, 9,12mm. For the optimum quality of these Tablet Making Machines, we have chosen as the most reliable manufacturer and supplier of Tablet Making Machines.

These machines are featured with :Automatic compression and ejection device
Revolution of the wheel drive
Automatic feed
Removal of tablets
Built on a heavy cast body

Eccentric pressure system

Easy setting for thickness and hardness of tablets

Nuts and lock nuts

Die and set of punches of chromium steel

Spare die & punches: extra die & punches of chrome steel of sizes 6,9and 12mm are provided at an extra cost (any one size)

Stand for tablet MACHINE: made of heavy angle iron

Manufacturers & Exporters

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



Tissue Homogenizer



Display Type
Speed Range
Power Rating
Power Supply
Operation Type
Motor Type
Impreller
Weight

Analog 0-4000 RPM 500 220V Electric operated AC Universal Tissue Glass Teflon Tube 10 Kg.

Package Contents

- Homogenizer
- Instruction Manual
- Stand
- Clamp
- Teflon Impeller

Manufacturers & Exporters

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131





TRAY DRYER (DIGITAL)

Product Details:

Material : Mild Steel

Temperature : 5 degree Ambient to 250°C

with accuracy +/-3°C

Voltage : 220 VAC

Indosati has achieved milestone in offering Tray Dryer Universal Digital to the clients. Tray Dryer Universal Digital is manufactured at multifaceted infrastructure facility using high quality spare parts and components. Offered range is widely demanded by chemical, petrochemical, food and beverage and many industries. This product has great technical air blower and have gives consistence performance. Offered range provides vacuum drying for non-flammable and flammable solvents and ensures safe drying without residues or oxidation.

Features:

Long service life
Easy to handle
Low maintenance

Specifications:

Standard double wall construction. Outer made of mild steel duly enamel painted or powder coated paint, inner made out of stainless steel sheet. Heating elements provided at bottom & two sides Temperature controlled by hydraulic type of thermostat or Digital temperature controller. It is provided with (HxWxD) (With two SS shelves.

Optional Accessories:
Air Circulation Fan
Timer 0 – 24 Hours
Digital Timer
Digital Temperature Indicator
Digital Temperature controller –cum- Indicator
Microprocessor PID Temperature controller –cum- Indicator in
LED a pacturers

	Alam A	TF	RAY DRYER	
9			INDO Carrent Land Explanation	SATI Per Francia
5				

	rechnical Detail	IS.		
L	Chamber size	Chamber size	No.	Capacity
n	(HxWxD)	$(H \times W \times D)$	of shelves	in Litres
	in mm	in Inches		
	300 x 300 x 300	012 x 12 x 12"	2	28
	350 x 350 x 350	014 x 14 x 14"	2	45
	400 x 400 x 400	016 x 16 x 16"	2	65
	450 x 450 x 450	018 x 18 x 18"	2	95
	600 x 450 x 450	024 x 18 x 18"	2	125
	600 x 600 x 600	024 x 24 x 24"	2	224
n	900 x 600 x 450	036 x 24 x 18"	2	252
	900 x 600 x 600	036 x 24 x 24"	2	336
	900 x 900 x 900		2	720

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



VACCUM PUMP OIL FREE



Description-

Capacity 15 Liter

Vacuum 22"HG

Pressure 25 PSIG

HP 1/16

Phase Single

Volts 230V

Temp. 55°C

RPM 1440RPM

Current 0.2

Oil Free 100%

Manufacturers & Exporters

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131



Water Bath Rectangular Thermostat





MODEL NO. - AB-53

It is double walled with inner chamber made of stainless and outer wall of M.S. sheet duly enamel painted. The gap between outer and inner walls is fitted with special grade glass wool insulation. The concentrate rings can be removed to accommodate containers of various sizes.

Temperature from ambient to 90 c +_ 0.5 c +_ is controlled by "EGO"/ "JUMO" GERMAN thermostat.

AVAILABLE SIZES:

- 0 300x250x100 m.m. (6 holes of 75 m.m dia)
- 0 300x405x100 m.m. (12 holes of 75 m.m dia)

THE INDO SATI INSTRUMENTS & CHEMICALS

MEDICAL LAB D, B&M PHARMACY COLLEGES/INSTITUTIONS

D & B D-U-N-S NUMBER -91-652-0568 Govt Reg. No.-NSIC/GP/NTP/2022/98624

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131





WATER STILL WALL MOUNTED



MODEL NO. - AB-36

The unit is recommended for making progeny free distilled water of a very high degree of purity. Made out of stainless steel ,special kettle element is fitted with ejection device /auto cut for safety of the element in case water supply is stopped . The cock fitted to the unit is of brass C.P. Distillation with or without FLANGE SYSTEM can be supplied. Unit with flange system can be opened for cleaning of condenser from time to time so as to ensure its long life. A wall mounting clamp is provided with the unit but with rubber tubing .Supplied with cord and plug to work on 220/230volts A.C. supply. Available in capacities of approx . 2 ,4,6&8 liters.

THE INDO SATI INSTRUMENTS & CHEMICALS

AN ISO 9001-2008 CERTIFIED CO

D & B D-U-N-S NUMBER -91-652-0568

Govt Reg No. NSIC/RJP/GP/I-0006/2011-12 eq to DGS&D

#3674, TIMBER MARKET, Ambala Cantt - 133 001 (INDIA)

Tel No.: 0091-171-4000131 / 4001131